



- CONT. RUBBER INSERT
- 0.060 ALUM. CENTER PLATE, CLEAR ANODIZED FINISH
- 1 OR 2-HOUR FIRE BARRIER PER UL TEST REPORT
- CONT. ALUM. BASE MEMBER, MILL FINISH
- CLIPS (FIELD INSTALLED)
- FASTENERS @ 20" O.C. MAX, BY INSTALLER
- CONT. ALUM. EXPOSED EXTRUSION CLEAR ANODIZED FINISH

NOTE: 1 HOUR CONSTRUCTION INDICATED  
2 LAYERS OF GYPSUM BOARD FOR 2 HOUR CONSTRUCTION

SCALE: 6"=1'-0"



**M.H. POWELL & CO., INC.**  
ARCHITECTURAL SEISMIC EXPANSION JOINT SYSTEMS

2313 YATES AVENUE | PHONE : (323) 887-0037  
COMMERCE, CA 90040 | FAX : (323) 887-0877  
WEB : www.mhpowell.net

**MODEL**  
**KH-5-4**

INTERIOR WALLS / CEILINGS  
Surface Mount

PROJECT : \_\_\_\_\_ PROJECT # : \_\_\_\_\_  
 LOCATION : \_\_\_\_\_ DATE : \_\_\_\_\_  
 ARCHITECT : \_\_\_\_\_  
 CUSTOMER : \_\_\_\_\_

PAGE #